



**VolkerHighways**

**30**

**SAFETY ZONE DIMENSIONS**  
 Permanent speed limit 30mph or less  
 Sideways safety zone 0.5m  
 Longways safety zone 0.5m  
 (Dimensions are minima)

Drawing Office			
DWG Number	VH7655	Date Surveyed	Customer
Revision	1	Date Drawn	11-06-24
Drawn By	PT	Phase Number	1 of 3
Survey By	Cust	Page Number	1 of 1
Checked By	BM		

- Area of Works
- Safety Zones
- Temp Traffic Signals
- 750mm Road Signs
- 750mm/1m Road Cones
- Pedestrian Barrier

**Site Details Address**

Reading Parapet  
 London Street  
 Reading  
 RG1 4SA  
 Road Closure/Diversion

- Drawing Notes**
- Do not scale from this drawing, all dimensions to be verified on site.
  - It will be the responsibility of the contractor to ensure that all temporary traffic management shall be in accordance with the Traffic Signs Manual chapter 8 2009, Safety at Street works 2013, Traffic Signs Regulations and General Directions 2016 and all current / relevant Health and safety legislation.
  - All signage placement will be subject to available safe working space and all signage will be secured / ballasted with straps or sandbags.
  - A minimum lateral safety zone of 0.5m will be maintained at all times.
  - A minimum running lane of 3.0m will be maintained for buses and HGV's and a minimum of 2.0m for cars and light vehicles.
  - A safe segregated working area will be provided and maintained at all times.
  - Minimum size of temporary signage will be 750mm.
  - Arifork system to be utilised where practicable.
  - A minimum of 1.0m to be maintained for pedestrian access.